



RENHOTEC GROUP LIMITED

****: 86-027-81296316

⊕ : www.renhotec.com ⋈ : info@renhotec.com

Headquarters(Wuhan): No.555 Wenhua Avenue, Hongshan District, Wuhan

430074, China

Factory(Dongguan): No.25 Ningjiang Road, Humen Town, Dongguan City

Guangdong Province, China

Factory(jiangmen): Building 5, Wanyang Zhongchuang City, Daze Industrial Park, Jiangmen City, Guangdong Province, China



PRODUCT **OVERVIEW**

仁昊伟业集团

RENHOTEC GROUP LIMITED

solution provider in the field of electrical, electronic and industrial connectors.

Renhotec supplies high quality products and provide professional services globally in the industry sectors such as telecommunications, industrial automation, automotive, instrument, railway, new energy, marine and offshore, machinery, etc. The company won the recognition from partners from the world.

By providing global customers with professional and reliable connectivity solutions, Renhotec is making contributions to creating a smart and interconnected world.



PRODUCT CATALOG

ON BOARD







RENHOTEC 产品展示/M5 Series



01



M5 Male Panel Mount

Receptacle, Rear Fastened

Unshielded, PCB, Straight





M5001

M5005

02 3/4

M5005

03 M5006

3/4

04

Pos No.

Product Describtion

Product Describtion

3/4

3/4

M5 Female Panel Mount

Receptacle, Front Fastened, Unshielded, PCB, Straight

M5 Female Panel Mount Receptacle, Front Fastened, Unshielded PCB, Straight

M5 Male Panel Mount Receptacle, Rear Fastened Unshielded, Solder Cup Straight

M5009 3/4

05

M5010

3/4


M5 Male Overmolded Cable, Solder Cup Single End, Straight

M5 Female Overmolded Cable, Solder Cup, Single End, Straight





RENHOTEC 产品展示/M8 Series



RENHOTEC 产品展示/M8 Series





M8 Male Overmolded Cable

Single End, Unshielded

Straight

13



M8 Female Overmolded

Cable, Single End

Unshielded, Straight



15

RHT-M8006

3/4



16

REPOSTNO.

Product Describtion

RHT-M8001 3/4/5/6/8

RHT-M8002 3/4/5/6/8

3/4

14

M8 Snap-in Male Cable Single End, Unshielded Straight

RHT-M8005

M8 Snap-in Female Cable Single End, Unshielded Straight



RENHOTEC 产品展示/M9 Series

01 02 03 04 RHT-634-3141 RHT-634-3177 RHT-634-3256 RHT-634-3179 Pos No. 3/4/5/6/8 3/4/5/6/8 3/4/5/6/8 3/4/5/6/8 M9 Male Cable Connector M9 Male Panel Mount M9 Female Panel Mount M9 Female Cable Connector Product Describtion Shielded, Solder Cup Shielded, Solder Cup, Straight Receptacle, Rear Receptacle Rear Straight Fastened, Unshielded Fastened, Unshielded Solder Cup, Straight Solder Cup, Straight



M9 Female Overmolded Product Describtion Cable, Single End, Unshielded, Straight

M9 Male Overmolded Cable, Single End Unshielded, Straight RENHOTEC

产品展示/M12 Series RENHOTEC



2/3/4/5/6/8

M12 Female Plastic Field

Wireable Assembly Plug

Screw Termination, Unshielded





RHT-634-3370

M12 Male Plastic Field

Wireable Assembly Plug

Screw Termination

Unshielded, Straight

05

2/3/4/5/6/8

Straight

02

06

2/3/4/5/6/8

RHT-634-3372

03

RHT-634-3373

2/3/4/5/6/8

M12 Female Plastic connector Assembly, Screw Termination Unshielded, Right Angle







M12 Male Plastic connector

Assembly, Screw Termination

Unshielded, Right Angle



RENHOTEC

RHT-634-3326 2/3/4/5/6/8

07

RHT-634-3327

08

04

2/3/4/5/6/8

M12 Female Metal Field



REPOSTNO.

Pos No.

Product Describtion

M12 Male Metal Field Wireable Assembly Plug Screw Termination, Shielded Straight

RHT-634-3324

2/3/4/5/6/8

M12 Female Metal Field Wireable Assembly Plug Screw Termination Shielded, Straight

RHT-634-3325

2/3/4/5/6/8

M12 Male Metal Field Wireable Assembly Plug Screw Termination Shielded, Right Angle

Wireable Assembly Plug Screw Termination Shielded, Right Angle





Pos No.

RENHOTEC 产品展示/M12 Series

with Flange, Solder Type

Straight

09 10 11 RHT-634-3091 RHT-634-3223 RHT-634-3291 RHT-634-3292 12 Pos No. 2/3/4/5/6/8/12 2/3/4/5/6/8/12/17 2/3/4/5/6/8/12 2/3/4/5/6/8/12 M12 Male Plastic Field M12 Female Plastic Field M12 Male Metal Field M12 Female Metal Field **Product Describtion** Wireable Assembly Plug Wireable Assembly Plug Wireable Assembly Plug Wireable Assembly Plug Solder Termination Solder Termination Solder Termination Solder Termination Unshielded, Straight Unshielded, Straight Shielded, Straight Shielded, Straight 13 RHT-634-1423 14 RHT-634-1314 15 RHT-634-1306 16 RHT-634-1185 Pos No. 2/3/4/5/6/8/12/17 3/4/5/8 3/4/5/8 3/4/5/8 M12 Male Panel Mount M12 Panel Mount, Male, Rear M12 Female Panel Mount M12 Panel Mount, Male Product Describtion


with Flange, Solder Type

Straight

Front Fastened, PCB

Mount, Straight

产品展示/M12 Series RENHOTEC











RENHOTEC

REIPOS NO.				
	EN	Dec	Min	

RHT-634-1390

3/4/5/8

RHT-634-1422

3/4/5/8

21

22

RHT-634-3021 23


2/3/4/5/6/8/12/17

RHT-634-3189

24



M12 Male, Panel Mount





M12 Female, Panel Mount Front Fastened, Solder Straight

M12 Female, Panel Mount, Rear Fastened Solder, Straight

M12 Male, Panel Mount Front Fastened, Solder Straight

Rear Fastened, Solder Type, Straight

Fastened, PCB Mount

Straight



RENHOTEC 产品展示/M12 Series

25 26 27 RHT-634-3154 RHT-634-3245 RHT-634-3308 RHT-634-3309 28 Pos No. 2/3/4/5/6/8/12 2/3/4/5/6/8/12/17 2/3/4/5/6/8/12/17 2/3/4/5/6/8/12/17 M12 Male, Panel Mount M12 Male, Panel Mount M12 Male. Panel Mount M12 Female, Panel Mount Product Describtion Front Fastened, PCB Rear fastened, Solder Type Front fastened, PCB Mount Front fastened, Solder Type Mount, Straight Straight Straight Straight 29 RHT-634-3392 30 RHT-634-3239 31 RHT-634-3255 32 RHT-634-3391 Pos No. 2/3/4/5/8/12 2/3/4/5/8/12 2/3/4/5/6/8/12/17 2/3/4/5/6/8/12/17 M12 Male, Panel Mount M12 Female, Panel Mount M12 Female, Panel Mount M12 Male, Panel Mount, Rear Product Describtion Front fastened, PCB Mount Rear fastened, PCB Mount Front Fastened, PCB Mount Fastened, Solder Type Right Angle Right Angle Straight, nylon shell Straight

产品展示/M12 Series RENHOTEC



Product Describtion

Wireable Assembly Plug Solder Termination, Shielded Straight

M12 X-Coding Male Field M12 X-Coding Female Field Wireable Assembly Plug, Solder Termination Shielded, Straight

M12 X-Coding Male Plug Crimp Termination Shielded, Straight


M12 X-Coding Female Plug Crimp Termination, Shielded Straight



RENHOTEC 产品展示/M12 Series

41 42 43 RHT-634-3219 RHT-634-3218 RHT-634-3298 RHT-634-3300 Pos No. 2/3 2/3 2/3 2/3 RM12 S-Coding Male Panel M12 S-Coding Female M12 S-Coding Male Panel M12 S-Coding Female Product Describtion Panel Mount Receptacle Mount Receptacle, Rear Panel Mount Receptacle Mount Receptacle, Front Rear Fastened, Unshielded Fastened, Unshielded, Solder Front Fastened, Unshielded Fastened, Unshielded Solder Cup, Straight Cup, Straight Solder Cup, Straight Solder Cup, Straight RHT-634-3306 RHT-634-3186 45 RHT-634-3187 46 47 RHT-634-3305 Pos No. 2/3/4 2/3 2/3 2/3/4 M12 S-Coding Male Field M12 S-Coding Female Field M12 L-Coding Female M12 L-Coding Male Panel Product Describtion Wireable Assembly Plug, Wireable Assembly Plug Panel Mount Receptacle Mount Receptacle, Rear Fasten, Unshielded, Solder Screw Termination, Power Screw Termination, Power Rear Fasten, Unshielded type, Unshielded, Straight type, Unshielded, Straight Solder Cup, Straight Cup, Straight

产品展示/M12 Series RENHOTEC





53







RENHOTEC

REIPOS NO.

M1204FS

3/4/5

RHT-634-3367 56

3/4/5

M12 Y Type Adapter, 1

55

Product Describtion

M12 4P Female, Molded Type Cable, Shielded

M12 4P Male, Molded Type Cable, Shielded

M12 Y Type Adapter, 1 Male to 2 Female

Female to 2 Male



RENHOTEC 产品展示/M16 Series

02

RHT-634-3385

01

2/3/4/5/6/7/8/12/14/16/19

RHT-634-3386

RHT-634-3383

RHT-634-3384

04

2/3/4/5/6/7/8/12/14/16/19

Product Describtion

Pos No.

M16 Male Cable Connector Shielded, Solder Cup Straight, PG

2/3/4/5/6/7/8/12/14/16/19

M16 Female Cable Connector, Unshielded Solder Cup, Straight, PG M16 Male Cable ConnectorUnshielded, Solder Type, Straight

2/3/4/5/6/7/8/12/14/16/19

M16 Female Cable Connector Unshielded, Solder Type Straight



RHT-634-3082

05 RHT-634-3085

06

RHT-634-4040

07

03

RHT-634-4041

2/3/4/5/7/8/12/14/16/19/24

Product Describtion

Pos No.

M16 Male Panel Mount Receptacle, Rear Fastened, Unshielded Solder Type, Straight

2/3/4/5/7/8/12/14/16/19/24

M16 Female Panel Mount Receptacle, Rear Fastened, Unshielded Solder Type, Straight

2/3/4/5/7/8/12/14/16/19/24

M16 Male Overmolded Cable, Unshielded, Solder Type, Straight

2/3/4/5/7/8/12/14/16/19/24

M16 Female Overmolded Cable, Unshielded, Solder Type, Straight



产品展示/M23 Series



01

05



M23 Male Straight Plug

Crimp Contacts E Layout



04

M623A-F

6/7/9/12/17/19

M23 Female Straight

Plug Crimp Contacts

M623A-M

6/7/9/12/17/19

M23 Male Straight Plug Crimp Contacts

02

M623K-M 6/7/9/12/17/19 M623H-F

03

6/7/9/12/17/19

M23 Female Panel Mounting Socket Unshielded Crimp Contacts









08

REPOS NO.

Product Describtion

Pos No.

Product Describtion

6/8

M923A

Contacts

M23 Power Circular Connectors Straight

Female Plug Crimp

M23 Power Circular Connectors Straight Male Plug Crimp Contacts

M923K

6/8

M23 Power Male Plug

M923D

6/8

06

Right Angled Crimp Contacts, 25.7 Flange

M23 Power Male Plug Right Angled Crimp Contacts 28.2 Flange



08

07

M923D1

6/8

RENHOTEC 产品展示/7/8" Series

78013

3/4/5/6

RENHOTEC





78014

3/4/5/6



02





03 78007 78005 04 3/4/5 3/4/5

Product Describtion

Pos No.

Connector, Unshielded, Screw Termination, Straight

Mini Change 7/8" Male Cable Remini Change 7/8" Female Cable Connector, Unshielded, Screw Termination, Straight

Mini Change 7/8" Male Panel Mount Receptacle Front Fastened, Unshielded Solder Cup, Straight

RENHOTEC

Mini Change 7/8" Female Panel Mount Receptacle, Rear Fastened, Unshielded, Solder Cup, Straight







RHT-634-3393

3/4/5

07

Pos No.

3/4/5

78001

05

78002

3/4/5

Mini Change 7/8" Male Product Describtion Overmolded Cable Unshielded, Solder Cup Straight

Mini Change 7/8" Female Overmolded Cable Unshielded, Solder Cup Straight

Mini Change 7/8" Female to Male Splitter Connector, T Type

RENHOTEC 产品展示/NMEA2000 Series



Gender	RENHOTEC	Female
Materials of Nut		Metal Or Plastic
Orientation		Straight
Locking Mechanism		Screw Locking
IP Rating		IP67

Gender	Male
Materials of Nut	Metal Or Plastic
Orientation	Straight
Locking Mechanism	Screw Locking
IP Rating	IP67









RENHOTEC



RENHOTEC



NMEA2000 Micro 90 Degree Elbow Adapter		
Gender	Male/Female	

Metal Or Plastic Materials of Nut Orientation Right Angle Locking Mechanism Screw Locking

IP67

Gender	Male/Female
Materials of Nut	Metal Or Plastic
The Port of the Tee connector	1 Port
Locking Mechanism	Screw Locking
IP Rating	IP67

RENHOTEC

RENHOTEC 产品展示/NMEA2000 Series

RENHOTEC





NMEA 2000 2 Way Tee Connector		
Gender	RENHOTEC	Male/Female
Materials of Nut		Metal Or Plastic
The Port of the Tee connector		2 Port
Locking Mechanism		Screw Locking
IP Rating		IP67

Gender	Male/Female
Materials of Nut	Metal Or Plastic
The Port of the Tee connector	3 Port
Locking Mechanism	Screw Locking
IP Rating	IP67







IP Rating





RENHOTEC



NMEA 2000 5 Way Tee Connec	ctor	
Gender		Male/Female
Materials of Nut		Metal Or Plastic
The Port of the Tee connector		5 Port
Locking Mechanism		Screw Locking
IP Rating		IP67

RENHOTES

RENHOTEC 产品展示/NMEA2000 Series

RENHOTEC

RENHOTEC





Gender	Male/Female
Materials of Nut	Metal Or Plastic
The Port of the Tee connector	6 Port
Locking Mechanism	Screw Locking
IP Rating	IP67

Gender	Male
Materials of Nut	Metal Or Plastic
Orientation	Straight
Locking Mechanism	Screw Locking
IP Rating	IP67

RENHOTE







REI

100







NMEA 2000 Mini Female Te	erminator
Gender	Female
Materials of Nut	Metal Or Plastic
Orientation	Straight
Locking Mechanism	Screw Locking

IP67

IP Rating

NMEA 20	00 Mini Single Tee C	connec	tor
Gender			Male/Female
Materials o	f Nut		Metal Or Plastic
The Port of	the Tee connector		1 Port
Locking Me	echanism		Screw Locking
IP Rating			IP67

RENHOTEC 产品展示/NMEA2000 Series



RENHOTEC



NMEA2000 Fema	le Pane	l Mount Co	onnector \	With cable
---------------	---------	------------	------------	------------

Gender	RENHOTECFemale
Materials of Nut	Metal
Plug Type	Micro (NMEA2000)
Locking Mechanism	Screw Locking
IP Rating	IP67
Cable Length	0.5m. 1m. 2m or Custom

Gender	Female
Materials of Nut	Metal
Plug Type	Micro (NMEA2000)
Locking Mechanism	Screw Locking
IP Rating	IP67

NMEA2000 Male Panel Mount Connector With cable

Cable Length





0.5m, 1m, 2m or Custom HOTEC

RENHOTEC





RENHOTEC

NMEA 2000 Backbone/Drop Cables		
Gender	Male/Female	
Materials of Nut	Metal Or Plastic	
Plug Type	Micro(NMEA2000)	
Locking Mechanism	Screw Locking	
IP Rating	IP67	
Cable Length	0.5m 1m 2m or Custom	

Gender	Male/Female
Materials of Nut	Metal Or Plastic
The Port of the Tee connector	4 Port/6 Port//8 Port
Locking Mechanism	Screw Locking
IP Rating	IP67
Cable Length	0.5m, 1m, 2m or Custom

RENHOTEC 产品展示/NMEA2000 Series





Gender	RENHOTEC Male/Female
Materials of Nut	Metal
Plug Type	Mini(NMEA2000)
Locking Mechanism	Screw Locking
IP Rating	IP67
Cable Length	0.5m, 1m, 2m or Custo

Gender	Male/Female	
Materials of Nut	Metal	
The Port of the Tee connector	2 Port	
Locking Mechanism	Screw Locking	
IP Rating	IP67	
Cable Length	0.5m, 1m, 2m or Custor	

产品展示/ Industrial Camera Cable





Cameralink Cable	
Connector Type	MDR/SDR 26 Pin
Orientation	Straight/Angled
Termination Type	Solder
Cable AWG	26/28 AWG or custom
Cable OD	9.5 mm or custom
Cable Specifications	Double shielded twisted pair PVC/PUR cable, also support custom
Applicable Brands	Basler, Sony, Hikvision, Dahua Daheng, JAI, AVT, PointGrey OMRON, Vieworks and so on
Cable Length	1M,3M,5M,10M or Custom

Cameralink Cable	-
Connector Type	Industrial RJ45 HOTEC
Orientation	Straight/Angled
Termination Type	Solder
Cable AWG	24/26 AWG or custom
Cable OD	6.5 mm or custom
Cable Specifications	Double shielded twisted pair PVC/PUR cable, also support custom
Applicable Brands	Basler, Sony, Hikvision, Dahua Daheng, JAI, AVT, PointGrey OMRON, Vieworks and so or
Cable Length	1M,3M,5M,10M or Custom

产品展示/ Industrial Camera Cable





I/O Cable	_
Connector Type	Hirose 6/8/10/12 Pin
Orientation	Straight/Angled
Termination Type	Solder
Cable AWG	24/26 AWG or custom
Cable OD	5.0/6.5 mm or custom
	Double shielded twisted pair
Cable Specifications	PVC/PUR cable, also support custom
HOTEC	Basler, Sony, Hikvision, Dahua
Applicable Brands	Daheng, JAI, AVT, PointGrey
	OMRON, Vieworks and so on
Cable Length	1M,3M,5M,10M or Custom

Industrial USB Cable	
Connector Type	USB2.0/3.0/3.1 / Micro B
Orientation	Straight/Angled
Termination Type	Solder
Cable AWG	24/26/28 AWG or custom
Cable OD	7.0 mm or custom

custom

Applicable Brands

Cable Length

Double shielded twisted pairENHOTEC PVC/PUR cable, also support

Basler, Sony, Hikvision, Dahua Daheng, JAI, AVT, PointGrey

OMRON, Vieworks and so on

1M,3M,5M,10M or Custom

RENHOTEC 产品展示/ Underwater Connectors

RENHOTEC











Subminiature Circular Se	eries 🔣
Gender	Male/Female
Durability Life	>500 cycling
Number of Contacts	23456 pin
Wire cross-section	0.5 / 0.3 / 0.2 mm ²
Working depth	6000 meters

Micro Circular Series	
Gender	Male/Female _
Durability Life	>500 cycling
Number of Contacts	2 - 21 pin
Wire cross-section	1 / 0.5 mm ²
Working depth	6000 meters

RENHOTES

RENHOTEC 产品展示/ Underwater Connectors

RENHOTEC









Gender	ENHOTEC Male/Female
Durability Life	>500 cycling
Number of Contacts	23456810121625Pir
Wire cross-section	0.5 / 0.3 / 0.2 mm ²
Working depth	6000 meters

High Power Series	
Gender	Male/Female
Durability Life	>500 cycling
Number of Contacts	2 3 4 Pin
Wire cross-section	6 / 4 mm²
Working depth	6000 meters

RENHOTES





RENHOTEC

RENHOTEC 产品展示/ Underwater Connectors

RENHOTEC









Micro Circular Network Se	ries 🔣
Gender	Male/Female
Durability Life	>500 cycling
Number of Contacts	8 13 Pin
Wire cross-section	23 / 24 AWG
Working depth	6000 meters

Gender	Male/Female
Durability Life	>500 cycling
Number of Contacts	1Pin
Wire cross-section	RG400/316 PUR coaxial cable
Working depth	6000 meters

RENHOTEC 产品展示/ Underwater Connectors











Gender	HOTEC Male/Female
Durability Life	>500 cycling
Number of Contacts	23456810121625Pi
Wire cross-section	0.5 / 0.3 / 0.2 mm ²
Working depth	6000 meters

High Power Series				
Gender	Male/Female			
Durability Life	>500 cycling			
Number of Contacts	2 3 4 Pin			
Wire cross-section	6 / 4 mm²			
Working depth	6000 meters			





RENHOTEC 产品展示/ Underwater Connectors

RENHOTED











Micro Flat Angled Series	
Gender	Male/Female
Durability Life	>500 cycling
Number of Contacts	7 9 12 pin
Wire cross-section	0.5 mm ²
Working depth	6000 meters

Standard Flat Angled Series	
Gender	Male/Female
Durability Life	>500 cycling
Number of Contacts	2 3 4 5 7 9 13 24 pin
Wire cross-section	1.34 / 1.0 mm ²
Working depth	6000 meters





RENHOTEC 产品展示/SP Series

RENHOTEC









Coupling Method	Thread Connect
Pin Number	1/2/3/4/5/6/7/8/9/1012
	15/16/17/20/24/26/35
Termination	Solder/Crimp/Screw
	SP11: I:3-4mm,II:4-6.5mm
	SP13:I:4-6.5,II:5-8mm
Cable OD	SP17:6-10mm
RENH	SP21:I:4.5-7mm,II:7-12mm, III:5-9mr
	SP29:I:9-13mm,II:13-16mm
Rated Current	3A/5A/10A/13A/15A/25A/30A/50A
Rated Voltage	125V/180V/200V/250V/400V/500V
Waterproof Grade	IP68

Coupling Method	Thread Connect RENHOTEC
Pin Number	2/3/4/5/7/9/10/12
Termination	Solder/Crimp/Screw
Cable OD	SP17:6-10mm SP21:l:4.5-7mm,ll:7-12mm,lll:5-9mm
Rated Current	3A/5A/10A/13A/15A/25A/30A/50A
Rated Voltage	125V/180V/200V/250V/400V/500V
Waterproof Grade	IP68







SP Series Plastic In-line Receptacle		SP Series Plastic Rear-nut Mount Receptacle	
Coupling Method	Thread Connect	Coupling Method	Thread Connect
Pin Number	1/2/3/4/5/6/7/8/9/10/12/15/16 17/20/24/26/35	Pin Number	1/2/3/4/5/6/7/8/9/10/12/15/16 17/20/24/26/35
Termination	Solder/Crimp/Screw	Termination	Solder/Crimp/Screw
Cable OD	SP11: I:3-4mm,II:4-6.5mm SP13:I:4-6.5,II:5-8mm SP17:6-10mm SP21:I:4.5-7mm,II:7-12mm,III:5-9mm SP29:I:9-13mm,II:13-16mm	Cable OD	SP11: I:3-4mm,II:4-6.5mm SP13:I:4-6.5,II:5-8mm SP17:6-10mm SP21:I:4.5-7mm,II:7-12mm,III:5-9mm SP29:I:9-13mm,II:13-16mm
Rated Current	3A/5A/10A/13A/15A/25A/30A/50A	Rated Current	3A/5A/10A/13A/15A/25A/30A/50A
Rated Voltage	125V/180V/200V/250V/400V/500V	Rated Voltage	125V/180V/200V/250V/400V/500V
Waterproof Grade	IP68	Waterproof Grade	IP68



RENHOTEC 产品展示/SP Series

RENHOTEC













SP Series 2 Hole Flange Mount Receptacle

SP Series 2 note Flai	ige Mount Receptacte
Coupling Method	Thread Connect
Pin Number	2/3/4/5/6/8/12/17
Termination	Solder/Crimp/Screw
	SP17:6-10mm
Cable OD	SP21:l:4.5-7mm,ll:7-12mm,lll:5-9mm
	SP29:I:9-13mm,II:13-16mm
Rated Current RENHOT	3A/5A/10A/13A/15A/25A/30A/50A
Rated Voltage	125V/180V/200V/250V/400V/500V
Metaurus 4 Our de	upon.

SP Series 4 Hole Flange MountReceptacle

Coupling Method	Thread Connect RENHOTEC
Pin Number	2/3/4/5/6/8/12/17
Termination	Solder/Crimp/Screw
	SP17:6-10mm
Cable OD	SP21:l:4.5-7mm,ll:7-12mm,lll:5-9mm
	SP29:I:9-13mm,II:13-16mm
Rated Current	5A/15A/25A/30A/50A
Rated Voltage	125V/180V/200V/250V/400V/500V
Waterproof Grade	IP68





RENHOTEC







Low Current Plastic HVIL Series	
Rated Current	20A/30A/45A/70A/80A/125A/150A
Rated Voltage	1000V DC
Minimum Mating Cycles	500 times
Wire Range	2.5mm²~35mm²
Number of Positions	1 Pin / 2Pin / 3Pin/ 4Pin/ 5Pin/ 6Pin
Orientation RENHOTEC	Straight
Body Material	Plastic
IP Degree	IP67B
Reference Standard	USCAR-2, USCAR-37

Low Current Metal HVIL	. Series
Rated Current	25A/35A/50A/70A
Rated Voltage	1000V DC
Minimum Mating Cycles	500 times
Wire Range	2.5mm²~10mm²
Number of Positions	2Pin / 3Pin/ 4Pin
Orientation	Straight
Body Material RENHOTEC	Metal
IP Degree	IP68(mated)
Reference Standard	USCAR-2, USCAR-37 LV-215, RoHS

RENHOTEC 产品展示/NEW ENERGY Series

rec





RENHOTEC

Rated Current	125A-250A
Rated Voltage	1000V DC
Minimum Mating Cycles	500 times
Wire Range	25mm²~70mm²
Number of Positions	1 Pin / 2Pin / 3Pin
Orientation	Straight / Right Angle
Material	Zinc alloy, PA66
IP Degree	IP67B or IP6K9K
Reference Standard	USCAR-2, USCAR-37, LV-215

High Current Metal HVIL	Series	
Rated Current	125A-500A	
Rated Voltage	1000V DC	
Minimum Mating Cycles	500 times	
Wire Range	25mm²~150mm²	
Number of Positions	1 Pin / 2Pin	
Orientation	Straight / Right Angle	RENHO
Material	Zinc alloy, PA66	
IP Degree	IP67B or IP6K9K	
Reference Standard	USCAR-2, USCAR-37, LV	-215





MINI MSD /	MSD		920
Connector Typ	ре	Plug / Socket	C
Position		2	
Mount Style		Front Mount / Rear Mou	ınt
Fuse Rated C	urrent	80A-630A	
ip Rating		IP67	
HVIL	RENHOTEC	Yes / No	

	New Energy Signal Connector	
	Orientation	Straight / Right Angle
	Number of Positions	1 Pin - 8Pin / 12Pin - 50Pin
	Rated Current	7A - 350A
	Wire Range	0.25mm2-16mm2
	Body Material	Metal
	IP Rating	IP67
	Key RENHOTEC	N Key/W Key/X Key/Y Key/Z Key
	Rated Voltage	DC 1000V
	Mechanical life	500 Times

RENHOTEC 产品展示/NEW ENERGY Series





HVPT Connector	
Number of Positions	1/2/3 positions
Orientation	Straight
Mount Style	Panel
Rated Voltage	1000V DC
Wire Range	25/35/50mm ²
Rated Current	125A~200A
IP Rating	IP67
Wiring method	Crimp

High Voltage DC Contact	tor
Rated Current	20A-600A
Rated Voltage	1000V DC
Coil Voltage	12V/24V/48V
Contact Arrangement Power Contacts	1 Form X (SPST-NO-DM)
Aux. Contact Form	NO
Contact Material	Copper With Silver Plating
Mechanical Lifetime	200,000 operations (without load)
Terminal Types	Male / Female M4/M6/M8 thread
Hermetically Sealing Type	Ероху



RENHOTEC



RENHOTEC





Working Pressure	0~1.6MPa
Liquid Types	Liquid Coolant, Deionized Water, ec
Mechanical Life Cycles	1,000 operations
Shell Material	Aluminum (hard anodized) Stainless steel
Nominal Flow Diameter (mm)	3mm, 5mm, 7mm, 8mm
Termination Type	Male Thread, Hose Connection Hose Connector - 90° angle, Flange
Maximum Flow Rate	2.1L/min, 7.3L/min, 13.9L/min
Leakage at Each Disconnect	≤0.02ml
Mating Force (N)	30-90

Connector Type	Vehicle End(female socket) Battery End(male socket)
Rated Voltage	1500V DC high voltage powe 300V low voltage signal
Rated Current	150A-400A
Protection Grade	IP67 (after mating)
Number of High Voltage Power Pin	2
Number of PE Pin	1
Number of Low Voltage Signal Pin	10/21/30
Floating	X, Y \pm 5mm, Z $+$ 0/-10mm Angle \leq 3°
Mating and Unmating Force	≤600N

RENHOTEC 产品展示/NEW ENERGY Series

RENHOTEC





RENHOTEC

Connector Type	Plug / Socket
Gender	Male / Female
Orientation	Straight / Right Angle
Number of Positions	1 Pin
Rated Current	60A-500A
Termination Style	Crimp
Wire Range	10mm2-150mm2
IP Rating	IP65/IP67
Color Option	Red / Black / Orange

Through Wall Power Terr	
Connector Type	Panel mount
Dielectric Voltage	3000V
Rated Voltage	1000VDC
Number of Positions	1 Pin
Rated Current	120A-500A
Termination Style	Inner Screw / Outer Screw RENHOTE
Thread size	M6/M8/M10
IP Rating	Non/IP67
Color Option	Red / Black



RENHOTE

44





Panel Feed-Through Barrier Terminal				
Rated Current	30A - 250A			
Rated Voltage	600V DC			
Mounting Type	Panel Mount			
Insulation Resistance	DC500V 1000MΩ below			
Wire Range	2.5mm ² ~80mm ²			
Number of Positions	1-12pin			
Pitch	11mm/13mm/16mm/21mm/27mm			
Operation Temperature	-40°C~+120°C			
Elama Retardant Grade	111.94-1/0			

Hybrid Connector	_
Rated Current	45A - 400A RENHOTEC
Number of Positions	2, 2+1, 2+2,,
Rated Voltage	DC 1000V
Wire Range	2.5mm² ~ 150mm²
Protection Rating	IP67
Contact Material	Copper
Temperature Range	-40°C~ +125°C
Salt Spray Resistance	144H(mating state)
Durability	500 times

RENHOTEC 产品展示/NEW ENERGY Series


RENHOTEC





Power Drawer Connect	or
Rated Current	35A/45A/65A/85A/125A/1
Contact pins	4P- 54P
Insulation Resistance	1000MΩ Below
Withstand Voltage	3000V/1000V
Mechanical Lifetime	1000 Times
Operating Temperature	-55℃~+125℃
Vibration	10-2000HZ (the acceleration of 147m
Terminal Style	Crimping/PCB tail/Colder

EV Charger	(10)		
Model	Type2 Series / GB/T Series SAEJ1772 Type1 Series / Chademo		
Connector Type	Plug / Receptacle / Adapter Extension cable / Dummy Socket		
Туре	AC / DC		
Rated Current	16A/32A/70A/80A/125A/200A/250A		
Rated Voltage	220v/480v REN	HOT	
Power	AC:3.5kw~22kw; DC: 60kw,90kw,120kw		
IP Degree	IP54		
Contact	Copper alloy,silver + thermoplastic on the top		
Durability	>10000 times		



RENHOTEC 产品展示/ON BOARD CHARGER Series

TEC



Input voltage range	96-265V
Input Frequency Range	45~65Hz
Output current	18A/25A/35A
Operating temperature	-40~55°C
Effiency	≥93%
Ripple Coefficient of Voltage	≤1%
Voltage Stabilization Accuracy	5%
Output Response Time	≤5S
Cooling Type	Air Cooling
Waterproof Rate	IP67

3.3KW		
Input voltage range	96-265V	
Input Frequency Range	45~65Hz	
Output current	30A/45A/60A	
Operating temperature	-40~55°C	
Effiency	≥93%	
Ripple Coefficient of Voltage	≤1% REN	HOTE
Voltage Stabilization Accuracy	5%	
Output Response Time	≤5S	
Cooling Type	Air Cooling	
Waterproof Rate	IP67	

RENHOTEC 产品展示/ON BOARD CHARGER Series

RENHOTEC 产品展示/ON BOARD CHARGER Series











6.6KW	
Input voltage range	96-265V
Input Frequency Range	45~65Hz
Output current	18A/44A/60A
Operating temperature	-40~55°C
Effiency	≥93%
Ripple Coefficient of Voltage	≤1%
Voltage Stabilization Accuracy	2%
Output Response Time	≤5S
Cooling Type	Air Cooling
Waterproof Rate	IP67

Portable OBC	
Input voltage range	185~2 <mark>70V</mark>
Input Frequency Range	45~65Hz
Output current	25A/30A/35A/40A/50A
Operating temperature	-20~55℃
Effiency	≥93%
Ripple Coefficient of Voltage	/
Voltage Stabilization Accuracy	7
Output Response Time	7
Cooling Type	Air Cooling
Waterproof Rate	IP65





Portable OBC	
Input voltage range	185~270V
Input Frequency Range	45~65Hz
Output current	25A/30A/35A/40A/50A
Operating temperature	-20~55 C
Effiency	≥93%
Ripple Coefficient of Voltage	/
Voltage Stabilization Accuracy	1
Output Response Time	7
Cooling Type	Air Cooling
Waterproof Rate	IP65

ZUKW	
Input voltage range	200~450V or 400~700V
Input Frequency Range	1
Output current	50A/250A
Operating temperature	-20~65°C
Effiency	≥92%
Ripple Coefficient of Voltage	/ RENH
Voltage Stabilization Accuracy	5%
Output Response Time	≤200mS
Cooling Type	Liquid Cooling
Waterproof Rate	IP67





汽车系列

Fakra Series / HSD Series Mini Fakra Series / H-MTD Series

ALIBABA CAMPUS C

You'll arrive

RENHOTEC 产品属性/HSD

RENHOTEC



	Characteristic Impedance	100Ω
	Frequency Range	DC~2GHz
	Withstanding Voltage	250 V rms
	Return Loss	≥20 dB 1GHz
	Insertion Loss	≤0.1×fGHz dB
RENI	Thisulation Resistance	≤ 0.1 dB, DC to 2 GH
	Number of plug-in times	25 cycles Min
	Snap retention force	110 N Min
	Pull-out force	5N Min

nsertion Force (non-waterproof single head)

30N Max

RENHOTEC 产品展示/HSD Connector

HSD PCB Plug Series


Z Code

HSD Plug Straight 4+4 Pin

Panel Mount Through Hole



RENHOTEC 产品展示/HSD Connector













Product Name

Product Describtion

HSD PCB Plug Series

HSD Jack Straight 4 Pin

Cable Mount Z Code

HSD PCB Plug Series

HSD Plug Straight 4 Pin

Cable Mount Z Code

HSD PCB Plug Series

Cable Mount Z Code

HSD Plug Straight 4+2 Pin

RENHOTEC 产品展示/HSD Cable



Hsd Z Code Plug To RJ45

Connector With Cable



02

06



03





Product Name

Product Name

Product Describtion

Product Describtion

HSD Cable Series

01

Pin To Hsd Z Code Female With RG174 Cable

HSD Cable Series

HSD Cable Series

Hsd Straight Z Code Male 4 Hsd Z Code Right Angle Female 4 Pin To Hsd Z Code

HSD Cable Series

Hsd Z Code Straight Female 4 Pin To Hsd Z Code 90 Male 180 Degree With 2m Cable Degree Male With 3m Cable







HSD Cable Series



05

HSD Cable Series

Crimp With Cable

HSD Cable Series

Gx12 Plug 4 Pin To Hsd Z

Code Plug 180 Degree

Crimp With Cable

HSD Cable Series

4 Pin To Hsd Z Code Male 4 4 Pin 180 Degreewith Pin Crimp With RG174 Cable Crimp 3m Cable

RENHOTEC

产品展示/HSD Cable





10



11



09

HSD Cable Serise

Straight With 2m Cable

HSD A Code 4 Pin Male To HSD A Code 4 Pin Female

Hsd A Code 4+2 Pin Female To Hsd A Code 4+2 Pin Female Straight Crimp With 50cm Cable Crimp With 20cm Cable

HSD Cable Serise

HSD Cable Serise

Hsd E Code 4 Pin Female To Rca Female Straight

HSD Cable Serise

Hsd H Code 4 +2 Pin Female To Hsd D Code 4+2 Pin Female Straight Crimp With 2m Cable





HSD Cable Serise

Product Describtion

REIProduct Name

Product Name

Product Describtion

Hsd B Code 4 +2 Pin Female To Hsd H Code 4+2 Pin Male And C Code 4 Pin Male Straight Crimp With 2m Cable















GX12 Plug 4 Pin To Hsd Z

Code Jack 180 Degree

RENHOTEC 产品属性/FAKRA







NHO:	TEC	

Fakra属性	
Characteristic Impedance	RENHOTEC 50Ω
Frequency Range	DC-6 GHz
Withstanding Voltage	800 Vrms
Return Loss	18 dB Min
Insertion Loss	≤0.1×fGHz dB
Insulation Resistance	1 GΩ Min
Number of plug-in times	25 cycles Min
Snap retention force	110 N Min
Pull-out force	2N Min
nsertion Force (non-waterproof single head)	25N Max

Characteristic Impedance	50Ω RENHOTEC
Frequency Range	DC-9 GHz
Withstanding Voltage	800 Vrms
Return Loss	25dB Min @DC-3 Ghz 20dB Min @3~6 Ghz
Insertion Loss	≤0.1×fGHz dB
Insulation Resistance	1000M Ω Min
Number of plug-in times	25 cycles Min
Snap retention force	110 N Min
Pull-out force (Four-port)	5 N Min
Insertion Force (Four-port)	60 N Max(Non-Waterpro Single Head)

产品展示/FAKRA Connector RENHOTEC

03

02









01

Fakra Cable Series

Fakra Cable Series

Fakra Cable Series

Fakra Cable Series

Product Describtion

Product Name

Fakra Plug Straight Male Pin Cable Black A Code Crimp

Fakra Plug Straight Male Pin Cable Bordeaux D Code Crimp

Fakra Plug Right Angle Male Pin Panel Mount Through Hole Blue C Code Solder

Dual Fakra Plug Right Angle Male Pin Panel Mount Through Hole Blue C Code Solder



05



RENH 06





07

08

04

REProduct Name

Fakra Cable Series

Fakra Cable Series

Fakra Cable Series

Fakra Cable Series

Product Describtion

Dual Fakra Jack Straight Female Pin Cable White B Code Crimp

Fakra Jack Straight Female Pin Cable Curry K Code Crimp

Dual Fakra Plug Straight Male Pin Cable Waterblue Z Code Crimp

Fakra+2 Male Z Code PCB Connector



RENHOTEC 产品展示/FAKRA Connector







10

02





Product Name

Product Describtion

Fakra Plug Right Angle Male Pin Panel Mount SMT Blue C Code Solder

Fakra PCB Series

Fakra PCB Series

Dual Fakra Plug Right Angle Male Pin Panel Mount SMT Waterblue Z Code Solder

Fakra Plug Right Angle Male Pin Panel Mount Through

Hole White B Code Solder

Fakra PCB Series

11

03

Fakra PCB Series

Fakra Male Waterblue Z Code Cable Mount

产品展示/Mini FAKRA connector









Product Name

Mini Fakra Series

Mini Fakra Plug Right Angle Product Describtion Male Pin Panel Mount Through Hole Black A Code Solder

Mini Fakra Series

Mini Fakra Plug Straight Male Pin Panel Mount Through Hole Waterblue Z Code Solder

Mini Fakra Series

Mini Fakra Plug R/A PCB Mount Single Hole Waterblue Z Code

Mini Fakra Series

Mini Fakra Plug R/A PCB Mount Two in One Waterblue Z Code

产品展示/Mini FAKRA Connector RENHOTEC





06

10





05

09

Mini Fakra Series

Mini Fakra+4 Plug PCB Mount Black A Code

Mini Fakra Series

Mini Fakra Female Single Cable Connector Waterblue Z Code

Mini Fakra Series

Mini Fakra Female Two in one Cable Connector Waterblue Z Code

Mini Fakra Series

TE Mini Fakra Female Four in one Cable Connector Waterblue Z Code

11

07







REIProduct Name

Product Describtion

Product Name

Product Describtion

Mini Fakra Series

Mini Fakra Male Single Cable Connector Waterblue Z Code

Mini Fakra Series

Mini Fakra Male Two in one Cable Connector Waterblue Z Code

Mini Fakra Series

Mini Fakra Male Four in one Cable Connector Waterblue Z Code



RENHOTEC 产品展示/FAKRA Cable













Product Name

Product Describtion

Fakra Cable Series

crimp with cable

Fakra A code plug straight

to MCX male right angle

Fakra Cable Series

01

02

06

Short Fakra Z Code Female Fakra Z code female straight to to Short Fakra R/A Z Code Fakra Z code jack crimp with cable

Fakra Cable Series

Fakra Cable Series

Dual Fakra+2 Female A Code to 2pcs Fakra+2 Female Connector with Cable





Female with Cable





05

Product Name

Fakra Cable Series

Fakra Cable Series

Fakra Cable Series

Fakra Cable Series

Product Describtion

Fakra D code female straight to Fakra D code male crimp with cable

Fakra Z code female right angle to Dual Fakra Z code straight male crimp with cable

Rosenberg Mini Fakra Z code male to 4 pcs Fakra A code plug straight crimp with cable

Fakra Z Code Female Waterproof Panel Mount to Fakra Z Code Female Crimp with Cable

RENHOTEC 产品展示/FAKRA Cable

Product Name

Product Describtion

10







09

Fakra Cable Series

Waterproof Fakra B Code

Female to Fakra B Code Male Crimp with Cable

Fakra Cable Series

Fakra Z Code Female to GX12 4P Male Crimp with Cable

Fakra Cable Series

11

Rosenberg Mini Fakra Z Code 4 pos Jack to 4* Fakra Z Code Female Crimp with cable

Fakra Z Code Female R/A to RCA Jack with Cable

Fakra Cable Series













RENHOTEC 产品属性/H-MTD







H-MTD属性	_
Characteristic Impedance	100Ω±5%(at 500 ps rise time)
Frequency Range	DC-20GHz
Withstanding Voltage	AC 250 V
Return Loss	30dB@DC-190 MHZ:20 dB @190-600 MH
Insertion Loss	0.137 dB @DC-190 MHZ.0.244 dB @190~600 MHz
Insulation Resistance RENHOTEC	500MO Min
Number of plug-in times	25 cycles Min
Snap retention force	110 N Min
Pull-out force	5N Min
Insert force	45N Max

RENHOTEC 产品展示/H-MTD Connector







04

01

H-MTD Series

02

H-MTD Series

H-MTD Series

Product Describtion

Product Name

H-MTD Single Straight Z code male for PCB

H-MTD Single Z code male for PCB

H-MTD Dual Z code male for PCB

H-MTD Quad Z code male for PCB

RENHOTEC 产品展示/H-MTD cable

H-MTD Series





02





01

H-MTD Series

03

Product Name

Product Describtion

H-MTD Series

H-MTD E6K14A-1CAZ5

Automotive Ethernet Cable

Assemblies, Single Ended Z

Code Female Cable, 150CM Female to A Code Male, 300CM

H-MTD E6K10D-1CAZ5 Automotive Ethernet Cable Assemblies, 4 in 1 Z Code

H-MTD Series

H-MTD E6K10D-1CAZ5 Automotive Ethernet Cable Assemblies,4 in 1 Z Code Female to Z Code Female,300CM Code Male Cable,300CM

H-MTD Series

H-MTD E6S10A-1CAZ5 Automotive Ethernet Cable Assemblies, Single Ended A

05

RENHOTEC 产品展示/H-MTD Cable











06





05

H-MTD Series

H-MTD Series

H-MTD Series

H-MTD Series

Product Describtion

Product Name

H-MTD E6S10A-1CAZ5 Automotive Ethernet Cable Assemblies, Single Ended A Code Female Cable,300CM

Rosenberger H-MTD E6K10D-1CAZ5 Automotive IVI System, Single Ended Z Code Female, 250CM

TE 2302510-9 MATEnet Automotive Ethernet Cabel Ethernet Cable Assemblies for Assemblies, A Code Male to Z code Female, 100CM

TE 2302510-9 MATEnet Automotive Ethernet Cabel Assemblies for ADAS System, B Code Male to Z Code Female, 50CM









09

10

11

07

H-MTD Series

Product Name

H-MTD Series

TE 2302510-9 MATEnet Product Describtion Automotive Ethernet Cabel Assemblies, C Code Male to

Z Code Female, 150CM

TE 9-1802105-9 MATEnet Automotive Ethernet Cabel Assemblies, A Code Male cable,250CM

TE 2302510-9 MATEnet Automotive Ethernet Cabel Assemblies, Z Code Female to Z Code Female,50CM

H-MTD Series

Rosenberger H-MTD Waterproof Quad female with cable




H-MTD Series



COAXIAL **SERIES**

同轴系列

Low-frequency Series / High-frequency Ser



SMP Female to SMP

Female Adapter 18GHz

2.4mm Female Connector

2 Hole Flange Solder Type

26.5GHz

2.92mm Female to 2.92

Female Adapter 40GHz

产品展示/BNC Series RENHOTEC







06





REN	Pr	OF	He	st N	Jan	ne.

Product Describtion

RHT-610-0225 **BNC Series**

BNC Waterproof Female

Connector for PCB

RHT-610-0312 **BNC Series**

Cable 75ohm

BNC Male Connector

Compression For RG6

RHT-610-5037

07 RHT-610-0004 08

BNC Series

RG316 Cable

BNC Series

Dual BNC Female BNC Female Connector 4 Hole Flange Solder for Connector Right Angled for PCB

05

Product Describtion

SMP Male Connector

Straight for PCB 40GHz

RENHOTEC 产品展示/F Series

01 02 03 04 RHT-611-0001 RHT-611-0024 RHT-611-0034 RHT-605-0503 Product Name F Series F Series F Series F Series F Female Connector Right F Female Connector F Male Connector F Male Connector Straight Product Describtion Angled for PCB Straight for PCB Compression for RG6 Through Hole for PCB Cable



05

RHT-611-0327

F Series

F Female Connector Product Describtion Waterproof Type Crimp for RG179 Cable 75ohm



RHT-611-0336

F Female Connector Edge

Mount For PCB

06 F Series

F Male Connector Right Angled for RG179 Cable

RHT-611-0308

F Series

07

RHT-611-0556

F Series

F Male Connector Compression for RG59 Cable

产品展示/Antenna Series RENHOTEC

03









01

05

Antenna Series

Auto GPS Antenna Polarization 50 Ohm 28 DBI with SMA Connector RG174 Cable

Antenna Series

2.4G 3 DBI FPC 50 Ohm Antenna With IPEX Connector 1.13 Cable **Antenna Series**

Auto GPS GSM Antenna Polarization 50 Ohm 28 DBI With SMA Connector RG174 Cable

Antenna Series

EB-201-0394

5 DBI High Gain SMA Male 433mhz Folding Rod Antenna







06

02



07



04

08

REPProduct Name

Product Name

Product Describtion

Antenna Series

Antenna Series

EB-201-2364

Antenna Series

Antenna Series

EB-201-2366

Omni Direction 2.4G 50

Product Describtio

VHF UHF 75 Ohm TV Antenna With SMA Male 1.5C2V Cable

75 Ohm HDTV Antenna Cleat Type F Connector With Amplifier

3dbi 50 Ohm SMA Male 2.4G Folding Rod Antenna


Ohm Wifi Fiberglass Antenna With N Male Connector



Product Name

08

RENHOTEC 产品展示/ TNC Series





产品展示/UHF Series RENHOTEC





UHF Series

for Cable

UHF Male Straight Clamp



UHF Male Straight Crimp

for Cable



		HE
	07	08
HF Series	UHF S	Series

UH

UHF Male Straight 4-hole Flange Solder for Cable

REPProduct Name

Product Describtion


UHF Series

Waterproof UHF Female

Straight Solder for Cable

Product Name

RENHOTEC 产品展示/ MCX Series



产品展示/Mini UHF Series RENHOTEC





Mini UHF Straight Female

Plated Brass Solder For

Cable

Bulkhead Waterproof Nickel





07



RENHOTEC

08

05 06 Mini UHF Mini UHF

Mini UHF Right Angle

Cable

Male Connector Crimp For

Mini UHF

RHT-630-0083

Mini UHF

Mini UHF Straight Female Bulkhead Nickel Plated

Brass Solder For Cable


Mini UHF Straight Female Gold Plated Connector Crimp For Cable

RENHOTEC 产品展示/ SMA Series





产品展示/SMB Series RENHOTEC





REPProduct Name

RG316

Product Name

Product Describtion

RENHOTEC 产品展示/ N Series

RHT-614-0231

N Type Connector

Solder RG178

Female 4 Hole Flange

N Series

01 02 03 04 RHT-805-0070 RHT-614-0146 RHT-614-0210 RHT-614-0199 Product Name N Series N Series N Series N Series N Type Connector N Type Connector N Type Connector Male N Type Connector Female Product Describtion Waterproof 4 Hole Flange Female Bulkhead Edge Female Waterproof Clamp for Cable TEC for PCB Mount 1.7mm Bulkhead Crimp RG174 05 06 08

RHT-614-0243

N Type Connector Female

Bulkhead Solder Cup

N Series

07

RHT-614-0241

N Type Connector Male

Straight Crimp for RG58

N Series

RHT-614-0253

N Type Connector Female

R/A Waterproof Crimp for

N Series

RG174













RENHOTEC

DIN Series

05 RHT-644-0014

06

EB-012-0005 07

EB-011-0006

08

DIN Series

DIN 1.6/5.6 Female

Product Describtion

DIN 1.0/2.3 Female Straight Bulkhead Through Hole

EB-010-0024

DIN Series

DIN 4.3/10 Female 4 Hole Flange Solder for Cable

DIN 7/16 Female Waterproof 4 Hole Flange for

DIN Series

Straight Crimp for Cable



Product Name


Product Describtion


产品展示/ Other RF (QMA TS9 SMC PAL) Series

01 02 03 EB-024-0016 Product Name Other RF Series-QMA Other RF Series-QMA Other RF Series-QMA Other RF Series-QMA QMA Male Right Angle QMA Female Right QMA Male Straight Crimp QMA Female Straight **Product Describtion** 4-hole Flange PCB Mount Crimp for Cable Angle 4-hole Flange for Cable RENHOTEC PCB Mount



产品展示/Other RF (QMA TS9 SMC PAL) Series













Product Name

RENHOTEC 产品展示/ RF Adapter Series

BNC Female to BNC

Female Adapter

RF Adapter Series

Flange

UHF Female to UHF

Female Adapter 4-Hole

01 RHT-612-0382 02 03 RHT-610-1045 RHT-627-0055 RHT-639-0691 Product Name **RF Adapter Series RF Adapter Series RF Adapter Series** RF Adapter Series



Product Describtion

ENHOTEC		
RHT-630-0109	05	RHT-612-0032



SMA Male to SMA Male

R/A Adapter

06 RHT-612-0032

RF Adapter Series

Female Adapter

SMA Male to 2 SMA



F Female to PAL Male

Adapter

07



Adapter

RF Adapter Series

TNC Female to TNC Female Waterproof Bulkhead Adapte

RHT-639-0678

RF Adapter Series



08

N Female to N Female

Waterproof Bulkhead

RENHOTEC 产品展示/RF cable Series



01



02



03



RHT-605-1814

RF Cable Series

R/A SMA RP Female to

R/A SMA RP Male for

RG178, L=10CM

RF Cable Series

RHT-605-1815

SMA Waterproof RP Female

to SMA RP Male for LMR 200. L=50CM

RF Cable Series

Four Holes Flange DIN

7-16 Female to DIN 7-16 Male for RG405, L=20CM RF Cable Series

Waterproof BNC Female to SMA Male for RG174, L=10CM









08

04

RF Cable Series

05

RF Cable Series RF Cable Series

RF Cable Series

R/A SMB Female to MMCX Male for RG178,

Product Describtion

REPProduct Name

Product Name

Product Describtion

R/A BNC Male to DC 3.5MM Male for RG174. L=40CM

BNC Male to SMC Female for RG316, L=30CM

Waterproof BNC Female to BNC Male for RG316, L=20CM

L=10CM







Product Name

Product Describtion



RENHOTEC 产品展示/ RF cable Series

RENHOTEC RENHOTEC 09 EB-002-0060 10 EB-002-0115 EB-002-0057 Product Name **RF Cable Series RF Cable Series RF Cable Series RF Cable Series** Four Holes Flange N Waterproof UHF Female TNC Male to R/A SMB Male R/A N Male to R/A MCX Product Describtion Male for RG316, L=20CM Female to TNC Male for to R/A MCX Male for for RG174; L=10CM RG174, L=20CM RG316, L=10CM



EB-002-0076

13 EB-002-0080

RF Cable Series

Product Describtion

Product Name

Ipex-1 to Ipex-1 for 0.81 cable, L=20CM

RF Cable Series

F Male to F Male for RG179, L=10CM

EB-002-0061 15

RF Cable Series

Waterproof SMA Female to Ipex-1 for 1.37 Cable, L=40CM

EB-002-0065

RF Cable Series

2.92MM Male to 2.92MM Male Cable, L=50CM























